


PRODUCT INFORMATION

MODEL: PH-355

PhaseMAXX Solid-State Phase Converters represent the ultimate technology for converting single-phase electrical power to three-phase electrical power. In fact, the three-phase power produced by PhaseMAXX is often superior in power quality to utility supplied three-phase.

PhaseMAXX utilizes the latest advances in solid-state power switching technology. Unlike rotary phase converters, it does not rely on a motor to generate a voltage. Proprietary software controls power switching devices that generate three-phase power with much more precision and efficiency. Its patented design makes it unlike any other phase converter.



POWER QUALITY

PhaseMAXX produces true sinusoidal three-phase output voltages balanced to within 1% under all load conditions. Because the output voltage is a sine wave with very low harmonic distortion, all types of three-phase equipment can be safely powered. Input current is true sinusoidal, near unity (0.99) power factor and does not produce harmonics which can pollute the power grid.

REGENERATIVE POWER CAPABILITY

PhaseMAXX converters handle regenerative power by passing clean, balanced power back onto the single-phase line when three-phase loads are in a generating mode. Most other power switching converters waste regenerative power by burning it up with braking resistors. Putting regenerative power back onto the line saves electrical power and even allows the PhaseMAXX to operate continuously as a three-phase to single-phase converter.

VERSATILITY

PhaseMAXX can safely power virtually any three-phase application within its rated capacity. It can power resistive and capacitive loads as well as motor or inductive loads. Its power quality makes it ideal for powering demanding loads such as CNC machine equipment, submersible pumps and other voltage sensitive applications rated either 50 or 60 Hz.

EASY INSTALLATION AND OPERATION

PhaseMAXX is available with built-in contactor and adjustable solid-state overload relay which allows it to function as a motor starter for most single-motor applications. It also has a control circuit and terminals, which allows an external switch to control both the converter and the load. Installation is straightforward and simple and can usually be accomplished in minutes with a minimum of equipment required.

ECONOMY

A utility three-phase service can cost thousands of dollars to install even when three-phase lines are nearby. PhaseMAXX is an affordable alternative that provides better phase balance than most utilities will specify for their service. It also protects three-phase equipment from damage due to under-voltage, over-voltage and single-phasing that can occur with AC mains power. PhaseMAXX is rugged, reliable and typically 97% efficient.

MODEL PH-355

FEATURES

- Balanced three-phase voltages
- High efficiency
- Electronic power factor correction
- High momentary overload current capacity
- Automatic brownout and over-voltage protection
- Fault protection and overload protection
- Built-in motor starter capability
- Clean power fed back to utility grid from three-phase generating loads
- 50 or 60 Hz input frequency allows operation anywhere in the world

SPECIFICATIONS

*Specifications are subject to change without notice

SINGLE-PHASE POWER

1-phase current characteristics	Sinusoidal, 2% total harmonic distortion
Power factor	Near unity, all load conditions (.99)
Voltage	187 – 260 volts
Recommended maximum 1-phase circuit breaker rating	110/125 amps

THREE-PHASE POWER

Rated HP	20
Rated Current Output	55
3-phase power characteristics	Sinusoidal, 3% total harmonic distortion
Phase-to-phase voltage balance	Better than 1% (NEMA MG1 standard for voltage Unbalance)
Voltage	Equal to single-phase input voltage – 187 – 260 volts
Maximum 3-phase current, steady state	64 amps
Overload current, 4 seconds	280 amps

Protective Functions

Under-voltage	Automatic shutdown <187 V, restart >199V
Over-voltage	Automatic shutdown >260 V, restart when <260V
Internal temperature sensor	Automatic shutdown if overheated

General

Efficiency	97% typical
Operating temperature range	-10 – 40 C
Storage temperature	-20 – 60 C
Weight	115 lb
Enclosure	Powder coated steel, Type 1 indoor or Type 3R rain proof, and power coated A1 with an EMI gasket
Dimensions (H x W x D)	Wall mount
Type 1 indoor	26 x 19 x 14 in.
Type 3R rainproof	30 x 19 x 14 in.

OPTIONS

Enclosure includes an EMI gasket and 3-stage EMI filtering
Plasma display with 36 character text for status indicators
Built-in motor starter for controlling single motor loads